



**SOKymOT**

**World Tag  
UNIQUE**

<b>Description</b>	The World Tag family allows an optimum price/performance ratio for a broad range of applications, such as process control and automation or indoor assets identification.		
	The <b>World Tag Unique</b> is equipped with a simple Read only 125kHz integrated circuit. The Unique chip contains a 40 bit unique number that guarantees the uniqueness of each tag.		
<b>Memory</b>	RO 64 bits		
<b>Electrical</b>	Operating frequency:	125 kHz ± 6 kHz	At room temperature
<b>Diameter</b>		<b>20</b>	<b>30</b>
<b>Physical</b>	Diameter:	20 mm ± 0.2 mm	30 mm ± 0.2 mm
	Thickness:	2.15 mm ± 0.25 mm	2.15 mm ± 0.25 mm
	Hole:	-	3.2 mm
	Weight:	0.8g	1.9g
	Material:	Polycarbonate	Polycarbonate
	Color:	Black	Black
<b>Mechanical</b>	Vibration	IEC 68.2.6	10g, 10...2000Hz, 3 axis, 2.5h
	Shock	IEC 68.2.29	40g, 18ms, 6 axis, 2000 times
<b>Chemical</b>	Resistant to	Water immersion IP 67 Aqueous solution of salts Unleaded gasoline Petroleum Mineral and vegetable oil	
<b>Part number</b>	Unique	601102	601103
			601104